

PDR 516 SL ROP [EL IGS]

Vented dryer, iron grey sides, electric

In SlimLine design, with residual moisture controls for perfect drying results.



- Drum volume 300.00 l, load size 12.0 kg–16.0 kg
- Very easy installation – only 711 mm wide
- Easy to move – direct access underneath
- Shortest cycles thanks to diagonal air flow
- Precision drying of all fabrics – PerfectDry

EAN: 4002516659594 / Material number: 12262520 /
Old Material Number: 52516001GB

Construction type and version	
Construction type	Front loader
Range	SlimLine
Front	Iron grey
Side panels	Powder-coated, iron grey
Fascia color	Stainless steel
Load size with a load ratio of 1:25	12.0
Load size with a load ratio of 1:18	16.0
Drum volume in l	300.00
Drying system	Exhaust air
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Stainless steel drum	•
Stainless steel honeycomb drum	No
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for laundrettes	•
Suitable for residential homes and apartments	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•
Performance data	
Maximum evaporation capacity in l/hour	12.5
Specific energy consumption in kWh/kg	0.55
Programme duration in min.	31
Control system	
Control system	M Select Benchmark
Programmability	Setting of defined parameters
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Control panel with easy-to-understand symbols	•
Standard electrical connection	
Heating type	Electric

PDR 516 SL ROP [EL IGS]

Vented dryer, iron grey sides, electric

In SlimLine design, with residual moisture controls for perfect drying results.



EAN: 4002516659594 / Material number: 12262520 /
Old Material Number: 52516001GB

Electrical connection	3N AC 400V 50/60HZ
Electric heater rating in kW	13.50
Total connected load in kW	14.10
Fuse rating in A	25

Dimensions and weight of dryer

External dimensions, height in mm	1800
External dimensions, width in mm	711
External dimensions, depth in mm	1089
External dimensions, gross height in mm	1810
External dimensions, gross width in mm	800
External dimensions, gross depth in mm	1180
Net weight in kg	145.7
Gross weight in kg	159
Maximum floor load in N	1664

Emissions data

Emission sound pressure level in the workplace	55 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	1.70

Features

Intelligent drum reversal	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
Retractable plinth	•
Communication slot	•
Machine-independent accessories	•

Efficiency

Recycling rate in %	96
---------------------	----

Connection options

Payment system (optional)	•
Optical interface for service access	•
Peak-load negotiation / energy management (optional)	•
WiFi	•
Connector Box	•
LAN module (optional)	•

Standards, test certificates and symbols

CE	•
VDE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
WEEE	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•