

PFD 101

Free-standing dishwasher

For large amounts of crockery in households, office tea rooms and utility areas.



- Wash performance: 13 place settings in just 36 min*
- Maximum final rinse temperature of 82 °C
- 13 % less energy consumption**
- Everything completely dry – AutoOpen assisted drying
- Flexible loading of load items for the best cleaning results

* Depending on site conditions (temperature of incoming water / power connection) values given may vary.

** Based on the ECO programme, compared to predecessor.



EAN: 4002516367017 / Material number: 11605560 / Old Material Number: 61010100GB

Construction type and version

Construction type	Freestanding dishwasher, front loader
Range	ProfiLine
Wash system	Fresh water front loader
Number of levels	2
Front	Brilliant white
Lid	Plastic
Side panels	Brilliant White
Fascia color	CleanSteel

Application

Suitable for guesthouses	•
Suitable for child care facilities	•
Suitable for universities and schools	•
Suitable for offices	•
Suitable for domestic use	•
Suitable for small businesses	•
Suitable for sports clubs	•

Performance data

Tested virucidal efficacy	•
Proven hygiene	•
Circulation pump Qmax in l/min.	75
Shortest programme duration in min.	36
Maximum final rinse temperature in °C	82
Cleaning performance, place settings/cycle	13
Service life in wash cycles	12500

Miele MOVE

Network-enabled with Miele MOVE	•
---------------------------------	---

Control system

Control system	Electronic controls
Programme selection	Programme selector buttons
Max. delay start in h	24
Time left display	•
Dishwashing programmes [number]	8
Adjustable final rinse temperature	•
Programme sequence indicator	•
Choice of display language	•
Check filter indicator	•

Standard electrical connection

Electrical connection	AC 230V 50HZ
Heater rating in kW	1.90
Total connected load in kW	2.10
Fuse rating in A	13
Length of mains connection cable in m	1.70
Provided with plug	•

Possible voltage variant 1

Electrical connection	AC 230V 50HZ
-----------------------	--------------

PFD 101

Free-standing dishwasher

For large amounts of crockery in households, office tea rooms and utility areas.



EAN: 4002516367017 / Material number: 11605560 / Old Material Number: 61010100GB

Heater rating in kW	6.10
Total connected load in kW	6.30
Fuse rating in A	32
Water connection/drainage	
Cold or hot water [number]	1
Required flow pressure in bar	1.00-10.00
Drain pump [DN]	22
Drain pump head height from floor level, max. in c	100
Integrated water softener	•
Maximum water hardness in mmol/l	6.50
Water protection system	Waterproof system
Length of water inlet hose in cm	150
Length of water drain hose in cm	150
Dimensions and weight	
External dimensions, height in mm	845
External dimensions with lid, height in mm	845
External dimensions, net width in mm	598
External dimensions, net depth in mm	600
External dimensions, gross height in mm	970
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	690
Usable space in wash cabinet, height in mm	540
Usable space in wash cabinet, width in mm	510
Usable space in wash cabinet, depth of upper baske	450
Usable space in wash cabinet, depth of lower basket in mm	450
In-feed height above floor in mm	210
Required niche width in mm	600
Net weight [kg]	56
Gross weight in kg	64
Maximum floor load in N/m ²	1000
Emissions data	
Emissions – sound pressure at workplace	33 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	0.0
Programmes	
Universal	•
Short	•
Hygiene	•
Cold/Pre-wash	•
Glasses	•
Plastics	•
Energy save/Eco	•
Intensive	•
Basket design	
ExtraComfort P baskets	•
Flexible FlexLine basket design	•
FlexCare glass holder [number]	2
FlexCare cup rack [number]	1
Cutlery basket	•
Height-adjustable upper basket	•

PFD 101

Free-standing dishwasher

For large amounts of crockery in households, office tea rooms and utility areas.



EAN: 4002516367017 / Material number: 11605560 / Old Material Number: 61010100GB

Combinable with APFD 210 bottle basket

•

Features

Drying

Extra drying, Active condensation drying, AutoOpen assisted drying

AutoClose

•

1 combi dispenser in the door for powder cleaning agent and rinsing agent

•

EcoFeedback

•

Safety lock

•

Brilliant GlassCare

•

Wash cabinet made from high-quality stainless steel

•

Optical interface

•

SmartStart

•

FlexiTimer with EcoStart

•

Efficiency

Load size of the ECO programme in place settings

13

Energy efficiency class (A–G)

E

Energy consumption of the ECO programme per 100 cycles in kWh

93

Water consumption of the ECO programme per cycle in l

12.0

Airborne noise emission rating (A–D)

C

Airborne noise emission in dB(A) re 1 pW

46

Programme running time of the ECO programme in min

250

Connection options

External dispensing module for liquid cleaning agent

•

WiFi

•

Standards, test certificates and symbols

CE

•

Complies with Machinery Directive 2006/42/EC

•

VDE

•

EMC radio suppressed

•

DIN EN 17735

•

EN 1717

•

Regulation 4 compliant

•

UKCA

•